

#### Document: #HT000085

### **Document Title: Add a TEC Printer to LabelView**

#### Product(s): Ti-1000

#### **Procedure:**

Begin the procedure by clicking on the **"Printer"** Button.



The Printer Dialog Box will be displayed. Click on "Add" Button.

lame	Port	<u>^</u>	Settings
doPDF v7	DOP7:		COM
Fax	SHRFAX:		COMIN
HP ePrint	LPT1:		Remove
Microsoft XPS Document Writer	PORTPROMPT:		
Parts	WSD-65990115		Add
Scheduling	192.168.0.163		Dect
Send To OneNote 2013	nul:		Port
Tec B472	->COM1:		
TEC B-472	COM4:		
ZDesigner 110Xi4 203 dpi (Copy 1)	USB002		
ZDesigner 110Xi4 600 dpi	USB001		
🖉 Zebra 110Xi4 (203dpi)	->USB001		
Žebra 110Xi4 (300dpi)	->USB001		
Žebra 110Xi4 (600dpi)	->USB001		
Cobro 110VITT Due (202dei)	STICPOOS	¥	

Scroll down Printer Model and click on the "TEC" folder.

А	dd printer	×
lodel	Port	
SATO     SATO Labeling     SATO Labeling     JALLYGENICOM     JALLYGENICOM     JARO     THARO     THERMOTEX     JARO     TIFLEX     JARO     TOSHIBA     JSC	<ul> <li>192.168.0.163</li> <li>192.168.0.35</li> <li>COM1:</li> <li>COM2:</li> <li>COM3:</li> <li>COM5:</li> <li>DOP7:</li> <li>FILE:</li> <li>LADA0:</li> <li>LADB0:</li> <li>LPT1:</li> </ul>	~
	Network prin	ters
	OK Cancel	Help

Select **"TEC B-472"**. Under Port Select the Port that is to be assigned to the TEC B-472 Print Driver. Click **"OK"**.

Model	Port
Tec B415 Tec B431 Tec B442 Tec B443 Tec B452 Tec B452 (600dpi) Tec B452 SLP Tec B452 SLP Tec B452 SLP (RFID) Tec B452 SLP (RFID) Tec B458 Tec B452 Tec B452	<ul> <li>▲ LADB0: LPT1: LPT2: LPT3: nul: PORTPROMPT: SHRFAX: Teklynx Driver Port: USB001 USB002 WSD-65990115-d92c-4333-b883-7f8fdi ♥</li> <li>▲ Network printers</li> <li>▲ TCP/IP</li> </ul>

When creating a new label or when checking existing label settings, click **"Label Set-Up"** Button.

	I EC 472 ZUS DPIJUI - LADELVIEW ZUTS -	- 110				
File	Edit View Object Data sources Tools Window Help					
* Nev	22 Jacobi Carlo	Form Zoom Zoom factor	Q Q Zoom - Zoom +	Zoom to Zoom to width	page	
	∔ 비 ! 止 非 耳   卑 ⑭   ⊨ 王   國 圓 麗   Ⅲ 💡					
	- ※ ※ 約 · (為 1) / ※ ※ ◆ 2 · (本 1) ▲ · · · · · · · · · · · · · · · · · ·			Label/Page	setun	×
<b>i</b> ,	■ I I I I I I I I I I I I I I I I I I I			, <u>-</u>		
TEC 4	72 203 DPI.Ibl		4 🚺 Stock	🔟 Label 🛄 F	Page Margi	ns 🖻 x
<u>م</u>	)	ահատհատհո	Type			× .
2 3			Name			~
-			Number of labels a		Preview	
1			Number of labels .	1		
-	Test Label #1 203 DPI		Label size :	4.000 x 2.500(inches)		
3						
-	TEC 472		Page size :	Customized 4.000 x		
-				2.500(inches)		
-			Background :			
Ξ			<none></none>	¥		
			Comment			
1	9007544402					
	0007044400				Save	Remove
1	Advanced-Poly Packaging Inc					
-						
-	(800) / 54-4403					
2 -			Settings	OK	Cancel	Help
1						
-						



Adjust the setting as displayed. Width should equal Print Head Width. Height is determined by label length.

			Y =		
Stock	Label 📗	] Page	Marg	jins	⊳
Туре				~	]
Name				~	]
Number of labels	s: 1	Γ	Preview		1
Label size :	4.000 x 2.500(inches)				
Page size :	Customized 4.000 x 2.500(inches)	-			
Background :					
<none></none>		¥			
Comment					
			0	0	
			save	Remove	
Collines			Grand		

Note: 1/4" to 3/8" of white space is required above first line of text and below last line of text.

	Label/Page	e setup	×
1 Li Stock	Label 📄 Pa	ge Margins	Þ
Label size(inches)		Preview	
Width	4.000		
Height	2.500		
Corner roundness	0.000		
Number of labels			
Per row	1		
Per column	1		
			۱ ۲
Settings	ОК	Cancel Hel	p



Check "Automatic Sizing" box.

Note: Page size needs to equal label size.

	Label,	/Page se	tup		×
4 Stock	Label	D Page	Margins		Þ
Automatic sizing					
- Page size(inches)		Pr	review		.
Customized		× [			
With	4.000	*			
Haide	2 500	*			
noger.	2.500	-			
A Orbait		L			
Cantoscap	e				
					.
Settings		ОК	Cancel	Help	

Click on "Settings" Button.

Adjust Settings as displayed by clicking on selection and making adjustments.

Printer settings - Tec B472	×
General Fonts	
General Send modified data only : <off> 180° rotation : <off> Flip (transparent media) : <off> Reverse overlayed objects : <off> Temperature : &lt;3&gt; Print speed : &lt;6.000(Inches)/s&gt; Detection : <none (continuous="" paper)=""> Advanced Cutter</none></off></off></off></off>	~
General Restore default settings	
OK Cancel	Help

Printer settings - Tec B472
General Fonts
Advanced Check printer status : <off> Adjust feed before printing : &lt;0.000(Inches)&gt; Adjust feed before printing : &lt;0.000(Inches)&gt; Timeout(s) : &lt;10&gt; Backfeed : &lt;0.000(Inches)&gt; Disable paper alignment feed : <off> Graphics optimization : <off> Automatic alignment : <on></on></off></off></off>
General Restore default settings
OK Cancel Help

Printer settings - Tec B472	×
General Fonts	1
Adjust feed before printing : <0.000(Inches)> Image format : <ascii> Imeout(s) : &lt;10&gt; Adjust feed sequence: Initialization sequence: Adjust feed : &lt;0.000(Inches)&gt; Disable paper alignment feed : <off> Graphics optimization : <off> Automatic alignment : <on> Format mode : <direct printing=""> Gap length between labels</direct></on></off></off></ascii>	<
General Restore default settings	
OK Cancel H	lelp

Printer settings - Tec B472	×
General Fonts	
General Advanced Cutter Cutter Cutter : <off> Adjust cut position Pages between cuts Eject last piece Control codes substitution Peel off</off>	
General Restore default settings	
OK Cancel Help	

Printer settings - Tec B472	×
General Fonts	- 1
General Advanced Advanced Cutter Substitution : <on> Substitution string for ESC : &lt;{&gt; Substitution string for LF : &lt; &gt; Substitution string for NULL : &lt;}&gt; Car off Peel off Car off</on>	~
General Restore default settings	
OK Cancel H	lelp

Printer settings - Tec B472	×
General Fonts	
General Advanced Cutter Cutter Control codes substitution Control codes substitut	
General Restore default settings	
OK Cancel Help	

Printer settings - Tec B472	×
General Fonts	1
General Advanced Advanced Cutter Cutter Control codes substitution Control codes substitution Peel off Peel off Peel off : <on> Peel off sensor : <o.000(inches)> Peel off sensor : <on> Memory card</on></o.000(inches)></on>	•
General Restore default settings	
OK Cancel He	þ

Printer settings - Tec B472	×
General Fonts	1
Advanced     Advanced     Advanced     Advanced     Outer     Control codes substitution     Pel off     Peel off     Memory card     Store in memory card : <off>     Memory card settings     Format memory card     Period     Ribbon</off>	*
General Restore default settings	
OK Cancel H	elp

Printer settings - Tec B472	×
General Fonts	
Cutter Control codes substitution Tear off Peel off Peel off Print mode : <thermal transfer=""> Ribbon Print mode : <o>&gt; Rewind motor : &lt;0&gt; Feed motor : &lt;0&gt;</o></thermal>	
General	
Restore default settings	
OK Cancel Help	

Click **"OK".** Save Print Drive and Label Setting to Label by Clicking **"Save"** in LabelView.